

Product Catalogue

**Swirl Diffuser** 


Type (SWD)




Swirl Diffuser products are manufactured by



44 Your comfort is our priority 77



www.khedr-eg.com



**Models** 

- SWD

**Finish** 

- Standard Finish - White



# **Model Design**

Khedr Model SWD Diffusers has fixed spiral blades that creates rotational as well as axial, Tangential and radial air Movement.

# Flow Pattern

SWD Diffusers produces a strong horizontal swirl allowing the supply air flow to rapidly mix room air.


# **Model Use**

SWD Diffusers are suitable to be used with applications like Offices, retails, Hotels and Fitness Gyms.



# - Dimensions

• Type (A)



Neck Size	Neck Si	ze (Inch)	Width	Height	factured
(Inch)	Round	Rectangular	(Inch)	(Inch)	
	Ø 6	6 x 6 23.8	23.8	9	are manu
24 × 24	Ø 8	8 x 8	23.8	11	Swirl Diffuser products are manufactured by Khedr Trust Co.
24 x 24	Ø 10	10 x 10	23.8	13	Diffuser p edr Trust
	Ø 12	12 x 12	23.8	15	Swirl [



# - Performance data

Neck Size		V <sub>K</sub> Outlet Velocity "FPM"											
"Inch"		200	300	400	500	600	700	800	900	1000	1100	1200	1300
	CFM	38	57	76	95	114	133	152	171	190	209	228	247
6 x 6	P <sub>T</sub>	0.004	0.012	0.022	0.034	0.049	0.067	0.087	0.106	0.126	0.155	0.188	0.129
or Ø 6	T	1-3	2-4	3-5	3-6	4-6	5-7	5-7	5-8	6-8	6-9	6-9	7-9
	NC	-	-	4	9	13	16	19	23	26	30	33	35
	CFM	68	101	135	169	203	237	271	304	338	372	406	440
8 x 8	P <sub>T</sub>	800.0	0.017	0.030	0.047	0.067	0.094	0.117	0.145	0.189	0.218	0.259	0.304
or Ø 8	T	2-3	2-4	3-5	3-7	4-7	5-8	5-9	6-9	7–10	7-10	7-11	8-11
	NC	-	6	12	17	21	27	31	35	38	40	41	43
10 10	CFM	106	159	211	264	317	370	423	476	528	581	634	-
10 x 10	P <sub>T</sub>	0.011	0.024	0.043	0.068	0.144	0.152	0.191	0.240	0.297	0.359	0.427	-
or Ø 10	Т	2-4	3-6	4-8	5-9	6-10	7-11	8-12	9-13	9-13	10-14	10-14	-
<b>J</b> .0	NC	-	10	16	21	28	34	36	40	42	44	46	-
40 40	CFM	152	228	304	380	457	533	609	685	761	837	-	-
12 x 12	P <sub>T</sub>	0.023	0.053	0.094	0.138	0.199	0.271	0.354	0.448	0.554	0.670	-	-
or Ø 12	T	3-5	4-8	5-10	6-11	8-13	9-14	10-15	11–15	12-16	12-17	-	-
,	NC	9	18	24	30	38	41	44	47	49	51	-	-

The minimum T Dimensions in feet is based on a  $V_{\scriptscriptstyle T}$  of 100 FPM , The Maximum T Dimension In feet is based on a  $V_{\scriptscriptstyle T}$  of 50.

T Throw "Feet"

 $V_{\kappa}$  Outlet Velocity "FPM"

NC re 8db room

 $P_{\tau}$  Total Pressure "Inch Water"



## - Selection Procedure

- 1. Determine the required CFM per each outlet as per cooling Load Calculation.
- 2. Determine the recommended Outlet Velocity  $V_k$  according to application as per following Table.
- 3. Select the size that give the required CFM at recommended outlet velocity from performance data tables.

Application	V <sub>K</sub> Outlet Velocity "FPM"	
Broadcast Studios	300-500	
Residences	500-750	ó
Apartments	500-750	Trust C
Mosques , Churches	500-750	y Khedr
Hotel Bedrooms	500-750	tured bi
Theaters	500-750	manufac
Private Offices, Acoustically Treated	500-750	cts are I
Private Offices, not Treated	500-800	ir produ
General Offices	1000-1250	Swirl Diffuser products are manufactured by Khedr Trust Co.
Dept. Stores	1500	Swir

Table (1) - Recommended Outlet Velocity \*

<sup>\*</sup> Table 20—Carrier Handbook - Part 2. Air Distribution - Chapter 3. Room Air Distribution—p.72



# - Selection Procedure Example

- 1. Required 250 CFM as per cooling load calculations.
- 2. The recommended outlet velocity ranges from 300 500 FPM.
- 3. The size of air outlet:

A. Size 10" X 10" at 400 FPM.

B. Size 12" X 12" at 300 FPM.

Neck Size		V <sub>K</sub> Outlet Velocity "FPM"					
"Inch"		200	300	400	500		
	CFM	106	159	211	264		
10 x 10	P <sub>T</sub>	0.011	0.024	0.043	0.068		
or Ø 10	Т	2-4	3-6	4-8	5-9		
	NC	-	10	16	21		
	CFM	152	228	304	380		
12 x 12	P <sub>T</sub>	0.023	0.053	0.094	0.138		
or Ø 12	T	3-5	4-8	5-10	6-11		
	NC	9	18	24	30		

## - How to oprder

Туре	SWD	Swril Diffser	
Material	А	A Aluminum S Steel	Trust Co.
Size	Ø	ø" lnch"	actured by Khedr
Finish	1	0 Aluminum 1 White Color 2 Other Colors	Swirl Diffuser products are manufactured by Khedr Trust Co.
Damper	0	O Without Damper 1 With Damper	Swirl Diffuser p



	Room Types	Noise Criteria (NC)
Residences, apartments	Living areas	30
	Bathrooms, kitchens, utility rooms	35
Hotels/motels	Individual rooms or suites	30
	Meeting/banquet rooms	30
	Corridors and lobbies	40
	Service/support areas	40
Office buildings	Executive and private offices	30
	Conference rooms	30
	Teleconference rooms	25
	Open-plan offices	40
	Corridors and lobbies	40
Courtrooms	Unamplified speech	30
	Amplified speech	35
Performing arts spaces	Drama theaters, concert and recital halls	20
	Music teaching studios	25
	Music practice rooms	30
Hospitals and clinics	Patient rooms	30
	Wards	35
	Operating and procedure rooms	35
	Corridors and lobbies	40
Laboratories	Testing/research with minimal speech Communication	50
	Extensive phone use and speech communication	45
	Group teaching	35
Churches, mosques, synagogues	General assembly with crical music programs	25
Schools	Classrooms	30
	Large lecture rooms with speech amplification	30
	Large lecture rooms without speech amplification	25
Libraries		30
ndoor stadiums, gymnasiums	Gymnasiums and natatoriums	45
	Large-seating-capacity spaces with speech, amplification	50

 $<sup>^{\</sup>star}$  ASHRAE Applications — Ch. 49 Noise and Vibration Control

## Other Products are provided by Khedr Trust Co.

### Diffusers & Grilles

- Squar Ceiling Diffuser
- Circular Ceiling Diffuser
- Slot Linear Diffuser
- Linear Bar Grille
- · Aluminum Grille
- Swirl Diffuser
- · Perfotrated Ceiling Diffuser · Disc Valve Diffuser
- Jet Diffuser
- · Eye Ball Diffuser
- Door Grille
- · Raised Floor Grid

### Louvers

- · Aluminum Louver
- · Sand Trap Louver

### Dampers

- Blade Volume Damper
- Toothed Wheel Volume Damper
- Gravity Shutter Damper

#### **Acoustics**

- Sound Attenuator
- Acoustic Louver

## Smoke Management

- Fire Damper
- Smoke Motorized Damper
- Smoke Vent

### **Duct Works**

- Galvanized Steel Duct
- Black Steel Duct
- Stainless Steel Duct
- Spiral Duct
- Flexible Duct
- Canavas
- Flanges
- · Flexible Duct Connector













Alganater Alkhairia roads.Industrial Area, Behind Cocacola Co., Cairo, Egypt Mailing Address: P.O.Box 13621, Cairo 11511 - Egypt

> Tel: +202 42452022 Mob: +2010 29999054 / +2010 29999056 +2010 29999057 / +2010 29999058

E-Mail: info@khedr-eg.com







